

LIYCY

Volgens DIN 47100

Litze: blank koper litze

Mantel: PVC, grijs

Isolatieweerstand: min 200 MΩ/km bij 20°C

Nominale spanning: 0,14 – 0,34mm² 250 V, 0,50mm² 500V

Beproevingsspanning: 0,14mm² 800V, >= 0,25mm² 1200V

Temperatuurbereik: statisch: -30°C tot +70°C
bewegend: -15°C tot +70°C

Afscherming: vertinde koperomvlechting



Aders	mm ²	CU kg/km	Artikelnr. 100m ring	Artikelnr. 500m hasp.
2	0,14	12,6	11500148	11500151
3	0,14	14,1	11500247	11500250
4	0,14	15,9	11500346	11500349
5	0,14	19,5	11500445	11500448
6	0,14	22,0	11500544	11500547
7	0,14	24,0	11500643	11500646
8	0,14	26,0	11500742	11500745
10	0,14	29,0	11500841	11500844
12	0,14	32,0	11500940	11500943

Aders	mm ²	CU kg/km	Artikelnr. 100m ring	Artikelnr. 500m hasp.
2	0,25	17,2	11501138	11501141
3	0,25	20,2	11501237	11501240
4	0,25	24,0	11501336	11501339
5	0,25	29,0	11501435	11501438
6	0,25	32,5	11501534	11501537
7	0,25	35,0	11501633	11501636
8	0,25	42,1	11501732	11501735
10	0,25	54,0	11501831	11501834
12	0,25	59,4	11501930	11501933

Aders	mm ²	CU kg/km	Artikelnr. 100m ring	Artikelnr. 500m hasp.
2	0,34	17,0	11502128	11502131
3	0,34	21,0	11502227	11502230
4	0,34	29,0	11502326	11502329
5	0,34	30,0	11502425	11502428
6	0,34	39,0	11502524	11502527
7	0,34	42,0	11502623	11502626
8	0,34	45,0	11502722	11502725
10	0,34	63,0	11502821	11502824
12	0,34	70,0	11502920	11502923

Aders	mm ²	CU kg/km	Artikelnr. 100m ring	Artikelnr. 500m hasp.
2	0,50	36,0	11503118	11503121
3	0,50	43,0	11503217	11503220
4	0,50	49,0	11503316	11503319
5	0,50	57,0	11503415	11503418
6	0,50	66,0	11503514	11503517
7	0,50	69,0	11503613	11503616
8	0,50	82,0	11503712	11503715
10	0,50	93,0	11503811	11503814
12	0,50	107,0	11503910	11503913

Andere kwadraturen en aderaantallen op aanvraag leverbaar.
Afwijkende verpakkingen op aanvraag.

Voor specificaties, neem contact met ons op!