

Neopreen kabels

H05/07RN-F



Litze: blanke koper litze volgens HD 383 klasse 5

Mantel: rubber, vlamdovend

Nominale spanning: 300/ 500V

Beproevingsspanning: 2kV

Temperatuurbereik: -25°C tot +60°C

Aders	mm2	CU kg/km	Artikelnr. 100m ring	Artikelnr. 500m hasp.
2	0,75	14,4	10800019	10800022
2	1,00	19,2	10800043	10800046
2	1,50	29,0	10800439	10800442
2	2,50	48,0	10800934	10800937
3	0,75	21,6	10800026	10800029
3	1,00	29,0	10800142	10800145
3	1,50	43,0	10800538	10800541
3	2,50	72,0	10801033	10801036
3	4,00	115,0	10801429	10801432
3	6,00	173,0	10801924	10801927
4	1,50	58,0	10800637	10800640
4	2,50	96,0	10801132	10801135
4	4,00	154,0	10801528	10801531
4	6,00	230,0	10802023	10802026
5	1,50	72,0	10800736	10800739
5	2,50	120,0	10801231	10801234
5	4,00	192,0	10801627	10801630
5	6,00	288,0	10802122	10802125
7	1,50	101,0	10800750	10800753
7	2,50	168,0	10801245	10801248
12	1,50	173,0	10800785	10800788
12	2,50	288,0	10801280	10801283

Ook leverbaar in de uitvoering H05/07RR-F

Voor specificaties, neem contact met ons op!