

Isolatiekapjes t.b.v. vlaksteker(hulzen)



Materiaal:

Standaard: PA66 UL94 V2
 Max. temp: 110°C
 Max voltage: 450V
 Glow wire test: 850°C




Fig. 1




Fig. 2



Fig.3 / 90°

Fig.	Artikelnr. Transp.	Artikelnr. Zwart	Geschikt voor: Vlaksteker/huls	Maat	Monteren	Verpakking stuks
1	49000201	49000207	huls	2,8	achter	40.000
1	49000213	49000219	huls	2,8	voor	50.000
1	49000249	49000255	huls	4,8	achter	35.000
1	49000354	49000355	huls	4,8	voor	25.000
1	49000381	49000382	huls	6,3	achter	22.500
1	49000445	49000446	huls	6,3	voor	15.000
2	49000225	49000231	steker	2,8	achter	15.000
2	49000361	49000362	steker	4,8x0,5	achter	10.000
2	49000368	49000369	steker	4,8x0,8	achter	10.000
2	49000396	49000397	steker	6,3	achter	15.000
3	49000237	49000243	huls	2,8	open	30.000
3	49000375	49000376	huls	4,8	zijkant	20.000
3	49000500	49000501	huls	6,3	open	12.500

Tevens verkrijgbaar:

- Platte uitvoering connectoren
- Zelf vastklemmende connectoren

Andere materialen en verpakkingen op aanvraag.

Voor specificaties, neem contact met ons op!