

Geïsoleerde adereindhulzen

Volgens DIN 46228 - deel 4



Isolatiemateriaal: polypropyleen (tot 105°C)

De pen is vervaardigd van vertind koper.

Z+F
Zoller+Fröhlich Elektrotechnik

Artikelnr.	mm ²	Penlengte in mm	Kleur	vpe stuks
40200050	0,14	6*	grijs	500
40200057	0,14	6*	bruin	500
40200064	0,14	8	grijs	500
40200071	0,14	8	bruin	500
40200078	0,25	6*	li.blauw	500
40200085	0,25	6*	violet	500
40200092	0,25	8	li.blauw	500
40200099	0,25	8	violet	500
40200106	0,25	12	li.blauw	500
40200113	0,25	12	violet	500
40200120	0,34	6*	turquoise	500
40200127	0,34	6*	rose	500
40200134	0,34	8	turquoise	500
40200141	0,34	8	rose	500
40200148	0,34	12	turquoise	500
40200155	0,34	12	rose	500
40200162	0,50	6	oranje	500
40200169	0,50	6	wit	500
40200176	0,50	8*	oranje	500
40200183	0,50	8*	wit	500
40200190	0,50	10	oranje	500
40200197	0,50	10	wit	500
40200204	0,50	12	oranje	500
40200211	0,50	12	wit	500
40200218	0,75	6	wit	500
40200225	0,75	6	grijs	500
40200232	0,75	6	li.blauw	500
40200239	0,75	8*	wit	500
40200246	0,75	8*	grijs	500
40200253	0,75	8*	li.blauw	500
40200260	0,75	10	wit	500
40200267	0,75	10	grijs	500
40200274	0,75	10	li.blauw	500

Artikelnr.	mm ²	Penlengte in mm	Kleur	vpe stuks
40200281	0,75	12	wit	500
40200288	0,75	12	grijs	500
40200295	0,75	12	li.blauw	500
40200302	1,00	6	geel	500
40200309	1,00	6	rood	500
40200316	1,00	8*	geel	500
40200323	1,00	8*	rood	500
40200330	1,00	10	geel	500
40200337	1,00	10	rood	500
40200344	1,00	12	geel	500
40200351	1,00	12	rood	500
40200358	1,50	6	rood	500
40200365	1,50	6	zwart	500
40200372	1,50	8*	rood	500
40200379	1,50	8*	zwart	500
40200386	1,50	10	rood	500
40200393	1,50	10	zwart	500
40200400	1,50	12	rood	500
40200407	1,50	12	zwart	500
40200414	1,50	18	rood	500
40200421	1,50	18	zwart	500
40200428	2,08	8*	geel	500
40200435	2,08	8*	blauw	500
40200442	2,08	12	geel	500
40200449	2,08	12	blauw	500
40200456	2,50	6	blauw	500
40200463	2,50	6	grijs	500
40200470	2,50	8*	blauw	500
40200477	2,50	8*	grijs	500
40200484	2,50	10	blauw	500
40200491	2,50	10	grijs	500
40200498	2,50	12	blauw	500
40200505	2,50	12	grijs	500

* standaard maatvoering

Voor specificaties, neem contact met ons op!

Geïsoleerde adereindhulzen

Volgens DIN 46228 - deel 4



Isolatiemateriaal: polypropyleen (tot 105°C)

De pen is vervaardigd van vertind koper.

Z+F
Zoller+Fröhlich Elektrotechnik

Artikelnr.	mm ²	Penlengte in mm	Kleur	vpe stuks
40200512	2,50	18	blauw	500
40200519	2,50	18	grijs	500
40200526	4,00	8	grijs	500
40200533	4,00	8	oranje	500
40200540	4,00	10*	grijs	500
40200547	4,00	10*	oranje	500
40200554	4,00	12	grijs	500
40200561	4,00	12	oranje	500
40200568	4,00	18	grijs	100
40200575	4,00	18	oranje	100
40200582	6,00	12*	zwart	100
40200589	6,00	12*	geel	100
40200596	6,00	12*	groen	100
40200603	6,00	18	zwart	100
40200610	6,00	18	geel	100
40200617	6,00	18	groen	100
40200624	10,00	12*	ivoor	100
40200631	10,00	12*	rood	100
40200638	10,00	12*	bruin	100
40200645	10,00	18	ivoor	100
40200652	10,00	18	rood	100
40200659	10,00	18	bruin	100
40200666	16,00	12*	groen	100
40200673	16,00	12*	blauw	100
40200680	16,00	12*	wit	100
40200687	16,00	18	groen	100
40200694	16,00	18	blauw	100

Artikelnr.	mm ²	Penlengte in mm	Kleur	vpe stuks
40200701	16,00	18	wit	100
40200708	25,00	16*	bruin	50
40200715	25,00	16*	geel	50
40200722	25,00	16*	zwart	50
40200729	25,00	18	bruin	50
40200736	25,00	18	geel	50
40200743	25,00	18	zwart	50
40200750	25,00	22	bruin	50
40200757	25,00	22	geel	50
40200764	25,00	22	zwart	50
40200771	35,00	16*	beige	50
40200778	35,00	16*	rood	50
40200785	35,00	18	beige	50
40200792	35,00	18	rood	50
40200799	35,00	25	beige	50
40200806	35,00	25	rood	50
40200813	50,00	20*	olijf	50
40200820	50,00	20*	blauw	50
40200827	50,00	25	olijf	50
40200834	50,00	25	blauw	50
40200841	50,00	30	olijf	50
40200848	50,00	30	blauw	50
40200855	70,00	21*	geel	25
40200862	95,00	25*	rood	25
40200869	120,00	30*	blauw	25
40200876	150,00	32*	geel	25

* standaard maatvoering

Voor specificaties, neem contact met ons op!